

1K Spray

Technical Data Sheet (TDS)

Product Description

Endura 1K Spray is Endura one component coatings packaged in easy to use aerosol.

Product features:

- Professional spray gun quality results
- Easy to Use
- No mess or measuring
- No equipment needed

Recommended Uses

Endura 1K spray is a high performance coating excellent for repairs or smaller painting projects.

Please read the Technical Data Sheet for specific product being sprayed for additional important suitability and surface preparation information.

Product Characteristics

Finish: varies by product

Volume Solids: Varies depending on product, please see specific product TDS for more information

Pot Life: 12 Hours @ 77°F (25°C) and 50% RH

VOC (EPA Method 24): varies by product

Shelf Life: 1 year

Current Endura 1K products

Endura 1K aerosols are currently available in the following products:

- V-Link
- P-Link

Using Endura 1K Spray

Shake can vigorously for 2 minutes minimum (after mixing ball rattles) before using.

Application Method

Once product is activated, do a test spray to check nozzle flow, substrate compatibility and color correctness. The spray fan can be adjusted for vertical or horizontal spray by turning the yellow nozzle orifice. Spraying distance is 8-10 inches from the surface being painted.

Clean Up

To prevent the nozzle from clogging, turn can upside down and spray nozzle until only propellant is being sprayed (approx. 2 seconds) between uses.

When work is finished, reverse aerosol and spray valve empty. The emptied aerosols are suitable for household collection.

Environmental Conditions

For optimum coating performance product, substrate and ambient temperature should be between 20°C-25°C* (68°F-77°F). To prevent condensation during application the surface temperature must be 3°C (5°F) or more above the dew point at all times.

*For use outside this range please contact your Endura representative.

Safety Precautions

Please refer to all Safety Data Sheets (SDS) before using this product. SDS sheets can be found on our website at www.endura.ca.